

Instructions for 2-1/2 cu/ft Portable Cement Mixer

- Always disconnect power before moving the Mixer
- Do NOT move the Mixer on the stand when there is material in the drum (must be empty)
- Setup MUST be on level ground
- Always start the Mixer **BEFORE** loading the drum with material.
- Discharge the mixer slowly while the drum is turning.
- Clean the Mixer immediately after each use and when buildup occurs.

How to Mix Concrete

1. You will need approx. 2 1/2 gallons of water.
2. 2-80 lb bags of pre-mix concrete
3. Start Mixer in motion **BEFORE** adding any material.
4. Add 2 gallons of water
5. Add 1-80 lb bag of pre-mix concrete
6. NOTE: Mixture will be very sloppy
7. Slowly add 2nd bag of concrete.
8. Add 1/2 gallon of water slowly to obtain desired thickness.

How to Mix Sand & Gravel

1. Use a 8 1/2 X 12" square shovel
2. Portland cement, gravel or round stone and masonry sand.
3. Start mixer in motion **BEFORE** adding any material
4. Put in 2 gallons of water.
5. Add 6 shovels full of gravel or round stone.
6. Add 2 shovels full of Portland cement.
7. Slowly add 4 shovels full masonry sand.

Always follow manufacturer's instructions for the product you are using if different from above.